

TTC Specs				Spline		Torque	Gear Ratios						Weight	Install	Lube/	
Part No.	Customer	Application	Engine	I	O	LB FT	1	2	3	4	5	6	Rev	Lbs.	Inches	Pints
T-5																
1352-000-191	GM	1969 "T" Truck	2.5L L4	14	27	230	4.03	2.37	1.49	1.00	0.72	NA	3.76	75	19.45	4.68
1352-000-208	Ford	Mustang 5.0 L 1992	5.0L V8	10	28	230	3.35	1.99	1.33	1.00	0.68	NA	3.15	75	23.99	5.62
1352-000-239	Ford	Mustang 1982-93	5.0L V8	10	28	233	3.35	1.99	1.32	1.00	0.68	NA	3.15	75	23.98	5.62
1352-000-246	Ford	Mustang 1994	5.0L V8	10	28	250	3.55	1.99	1.32	1.00	0.68	NA	3.50	75	23.98	5.62
1352-000-247	GM	Camaro/Firebird 96	3.8L V8	26	27	230	3.75	2.19	1.41	1.00	0.72	NA	3.53	70	24.36	6.75
1352-000-251	Aftermarket (Ford)	Mustang 1993 and prior	5.0L V8	10	28	300	2.95	1.94	1.34	1.00	0.63	NA	2.76	75	23.98	5.62
1352-000-260	Ford	Mustang 1999	3.8L V8	10	28	300	3.35	1.99	1.33	1.00	0.68	NA	3.15	74	23.98	5.62
TTET1239	TVR	TVR 1999	4.3L V8	23	27	230	2.95	1.94	1.34	1.00	0.80	NA	2.76	75	24.30	5.62
T-45																
1381-000-001	Ford	Mustang GT	4.6 2V	10	31	325	3.37	1.99	1.33	1.00	0.67	NA	3.22	104	31.63	6.50
1381-000-002	Ford	Mustang Cobra	4.6 4V	10	31	325	3.37	1.99	1.33	1.00	0.67	NA	3.22	104	31.63	6.50
1381-000-011	Ford	Mustang GT and Cobra 1999	4.6 4V	10	31	325	3.37	1.99	1.33	1.00	0.67	NA	3.22	104	31.63	6.50
TR-3650																
TCET1265	Ford	Mustang GT	4.6 2V	10	31	360	3.37	2.00	1.31	1.00	0.67	NA	3.37	119	31.61	8.02
TCET2018	Ford	Mustang GT	4.6 2V	10	31	360	3.37	2.00	1.31	1.00	0.62	NA	3.37	119	31.61	8.02
TCET4783	Ford	Mustang GT	4.6 2V	10	31	360	3.37	2.00	1.31	1.00	0.62	NA	3.37	119	31.61	8.02
T-56																
1386-000-011	Aftermarket	F-Car		26	27	400	2.97	2.07	1.43	1.00	0.80	0.62	3.28	110	26.26	8.13
1386-000-012	Aftermarket	Mustang	5.0L V8	10	31	400	2.97	2.07	1.43	1.00	0.80	0.62	3.28	129	32.47	8.13
1386-000-016	GM	F-Car 1993-97	5.7L LT1	26	27	350	2.66	1.78	1.30	1.00	0.74	0.50	2.90	129	29.81	8.13
1386-000-017	GM	F-Car 1998	5.7L LS1	26	27	350	2.66	1.78	1.30	1.00	0.74	0.50	2.90	129	29.81	8.13
1386-000-020	GM	F-Car 1999 (Hurst Shifter)	5.7L LS1	26	27	350	2.66	1.78	1.30	1.00	0.74	0.50	2.90	130	29.81	8.13

1386-000-023	GM	Corvette C5	5.7L LS1	26	27	375	2.66	1.78	1.30	1.00	0.74	0.50	2.90	115	19.29	7.31
TUET1259	Ford Aftermarket	Cobra-R (Mech. Speedo)	4.6 2V	10	31	400	2.97	2.07	1.43	1.00	0.80	0.62	3.28	115	32.47	8.13
TUET1260	Ford Aftermarket	Cobra-R (Elec. Speedo)	4.6 2V	10	31	400	2.97	2.07	1.43	1.00	0.80	0.62	3.28	115	32.47	8.13
TUET1694	Ford	Cobra	4.6L 4V	10	27	425	2.66	1.78	1.30	1.00	0.80	0.62	2.90	115	32.47	8.13
TUET2062	DCX - Service	Viper (One Piece C/S)	V10	26	30	550	2.66	1.78	1.30	1.00	0.74	0.50	2.90	110	27.15	8.13

TKO

TCET4615	Ford	Aftermarket		10	31	500	3.27	1.96	1.34	1.00	0.68	NA	3.00	105	31.24	5.28
TCET4616	GM	Aftermarket		26	31	500	3.27	1.96	1.34	1.00	0.68	NA	3.00	105	31.24	5.28
TCET4617	Ford	Aftermarket		26	31	600	2.87	1.89	1.28	1.00	0.82	NA	2.56	105	31.24	5.28
TCET4618	GM	Aftermarket		26	31	600	2.87	1.89	1.28	1.00	0.82	NA	2.56	105	31.24	5.28
TCET5008	Ford	Aftermarket		26	31	600	2.87	1.89	1.28	1.00	0.64	NA	2.56	105	31.24	5.28
TCET5009	GM	Aftermarket		26	31	600	2.87	1.89	1.28	1.00	0.64	NA	2.56	105	31.24	5.28

Actual torque rating are affected by vehicle weight, tire type and size, clutch and pressure plate, and driving style.

Recommended Fluid type - TKO transmissions GM Synchronesh (GM part# 12345349).

All other transmissions Dexron III or similar ATF fluid.